

## Supplementary Materials

Three algorithms (creeping random search, simulated annealing, and pseudo-derivative) used in projection pursuit guided tour optimisation are:

---

**Algorithm 1:** Creeping random search (CRS)

---

**input :**  $f(\cdot)$ ,  $\alpha_1$ ,  $l_{\max}$ , cooling

**output:**  $\mathbf{A}_l$

```
1 Generate random start  $\mathbf{A}_1$  and set  $\mathbf{A}_{\text{cur}} := \mathbf{A}_1$ ,  $I_{\text{cur}} = f(\mathbf{A}_{\text{cur}})$ ,  $j = 1$ ;  
2 repeat  
3   Set  $l = 1$ ;  
4   repeat  
5     Generate  $\mathbf{A}_l = (1 - \alpha_j)\mathbf{A}_{\text{cur}} + \alpha_j\mathbf{A}_{\text{rand}}$  and orthogonalise  $\mathbf{A}_l$ ;  
6     Compute  $I_l = f(\mathbf{A}_l)$ ;  
7     Update  $l = l + 1$ ;  
8   until  $l > l_{\max}$  or  $I_l > I_{\text{cur}}$ ;  
9   Update  $\alpha_{j+1} = \alpha_j * \text{cooling}$ ;  
10  Construct the geodesic interpolation between  $\mathbf{A}_{\text{cur}}$  and  $\mathbf{A}_l$ ;  
11  Update  $\mathbf{A}_{\text{cur}} = \mathbf{A}_l$  and  $j = j + 1$ ;  
12 until  $\mathbf{A}_l$  is too close to  $\mathbf{A}_{\text{cur}}$  in terms of geodesic distance;
```

---

---

**Algorithm 2:** Simulated annealing (SA)

---

```
1 repeat  
2   Generate  $\mathbf{A}_l = (1 - \alpha_j)\mathbf{A}_{\text{cur}} + \alpha_j\mathbf{A}_{\text{rand}}$  and orthogonalise  $\mathbf{A}_l$ ;  
3   Compute  $I_l = f(\mathbf{A}_l)$ ,  $T(l) = \frac{T_0}{\log(l+1)}$  and  $P = \min \left\{ \exp \left[ -\frac{I_{\text{cur}} - I_l}{T(l)} \right], 1 \right\}$ ;  
4   Draw  $U$  from a uniform distribution:  $U \sim \text{Unif}(0, 1)$ ;  
5   Update  $l = l + 1$ ;  
6 until  $l > l_{\max}$  or  $I_l > I_{\text{cur}}$  or  $P > U$ ;
```

---

---

**Algorithm 3:** Pseudo-derivative (PD)

---

```
1 repeat  
2   Generate  $n$  random directions  $\mathbf{A}_{\text{rand}}$  ;  
3   Compute  $2n$  candidate bases deviate from  $\mathbf{A}_{\text{cur}}$  by an angle of  $\delta$  while ensuring orthogonality;  
4   Compute the corresponding index value for each candidate bases;  
5   Determine the search direction as from  $\mathbf{A}_{\text{cur}}$  to the candidate bases with the largest index value;  
6   Determine the step size via optimising the index value on the search direction over a 90 degree  
   window;  
7   Find the optimum  $\mathbf{A}_{**}$  and compute  $I_{**} = f(\mathbf{A}_{**})$ ,  $p_{\text{diff}} = (I_{**} - I_{\text{cur}})/I_{**}$ ;  
8   Update  $l = l + 1$ ;  
9 until  $l > l_{\max}$  or  $p_{\text{diff}} > 0.001$ ;
```

---